


Electron-Hole Separation with Dual Electron/Hole Acceptors for Organic Photovoltaic Applications

Wei Li Wang, Georgios A. Tritsaris,
Elton Santos, and Efthimios Kaxiras

Harvard University

MRS 12/02/2013



Organic Solar Cells



Cost

Cheap and flexible



Boda Boda Operator



Efficiency

Polymer-fullerene bulk heterojunction solar cells (PSCs) approaching 10%



Hoppe, H.; Sariciftci, N. S. *J. Mater. Res.* **2004**, *19*, 1924–1945.

He, Z.; Zhong, C.; Su, S.; Xu, M.; Wu, H.; Cao, Y. *Nat. Photonics* **2012**, *6*, 591–595.


<http://www.afrigadget.com/2009/09/05/a-wearable-flexible-solar-panel-idea/>

Heterojunctions with Donor-Acceptor



Electron acceptor
High electron affinity



Electron-donor



Graphene as Anode Material



- Low cost, transparency, high electrical conductivity, chemical robustness, Flexibility.
- Impact on hole dynamics.

Park, H.; Brown, P. R.; Bulović, V.; Kong, J. *Nano Lett.* **2012**, 12, 133–140.

Wang, Y.; Tong, S. W.; Xu, X. F.; Özyilmaz, B.; Loh, K. P. *Adv. Mater.* **2011**, 23, 1514–1518

Calculation Methods


DFT (Siesta):

- Double- ζ plus polarization basis set
- 0.04 eV/Å maximum force convergence criterion
- Mesh cutoff of 200 Ry
- VDW (DRSLL) Van der Waals exchange-correlation density functional

TDDFT (GPAW):


- Absorption spectrum: Casida's formulation of time-dependent DFT (TDDFT) linear response theory
- Evolution of the photo-excited electron-hole pair: non-adiabatic Ehrenfest molecular dynamics
- Periodic boundary conditions used to avoid any spurious finite size effects

Sandwich Structure



Dia. Variation <1%

C60




ZnPc




3.0 Å

3.4 Å


Graphene



Potential Profiles across the Sandwich Structure




Pumping mechanism with dual electron/hole acceptors




TDDFT: 2.8 eV
DFT: 2.3 eV

Dynamics of Electron and Hole Transfer



Comparison between Various Interface Morphology



The flat configuration (b) is favored due to stronger coupling and asymmetric barriers

Summary

- Dual electron/hole acceptors for high efficiency
- Graphene is a promising hole collecting anode material
- The flat configuration for G/ZnPc/C60 structure is favored



Acknowledgment

Dr. Georgios A. Tritsaris Harvard University, SEAS

Dr. Elton Santos (Stanford University)

Prof. Efthimios Kaxiras Harvard University, Physics and SEAS